

# A Case Study to Automate Demand Response on a University Campus

T.M. Lawrence, J. Mohammadpour,  
S. Aghniaey



College of Engineering  
**UNIVERSITY OF GEORGIA**

R.T. Watson, M.C. Bourdreau



Terry College of Business  
**UNIVERSITY OF GEORGIA**

J. Hill – Southern Company Services



Organisers:



International Co-owners:



Sustainable Buildings  
and Climate Initiative  
Promoting Policies and Practices for Sustainability



Global Alliance  
for Buildings and  
Construction

# Outline

- Overview of smart grid, automated demand response (ADR)
- Challenges with ADR in existing buildings
- Methods to implement demand response
- Applications to a university campus



Organisers:




International Co-owners:



Sustainable Buildings and Climate Initiative  
Promoting Policies and Practices for Sustainability



# Grid Integration of the Future



# Demand Response Scenarios

## A. High Demand Relative to Supply:

- ❑ Reduce peak demand during high load conditions or grid “stress”
- ❑ Typically a summer cooling issue (occasionally in winter heating in some locations)

## B. High or Variable Supply Relative to Demand:

- ❑ How to manage peak production from distributed generation systems (renewable, CHP)?
- ❑ Germany starting in 2013;  
Becoming more common in parts of U.S. (Texas wind; CA solar)

## C. Managing for Low Carbon Energy Production:

- ❑ Management of demand to match type of supply available



Organisers:



International Co-owners:



Sustainable Buildings and Climate Initiative  
Promoting Policies and Practices for Sustainability



# Challenges with Existing Buildings on a Typical Campus

- ADR involves sophisticated communication and control capability
- Variability of building types, control systems
- Cost to upgrade legacy control systems
- Smart grid control features becoming available at the component or subsystem level



Organisers:



International Co-owners:



Sustainable Buildings and Climate Initiative  
Promoting Policies and Practices for Sustainability



# Execution of Demand Response

- Buildings typically contain both deferrable and non-deferrable electric loads for the same end-users.
- Key questions to answer:
  - What to curtail?
  - How long?
  - How to verify (and who does the verifying)?
  - Comfort considerations
  - Safety, security concerns
  - Control and monitoring
- Externally generated versus internally created events:
  - External by utility or outside agent
  - Internal at owner's discretion (demand limiting or peak shaving) - May be more effective

# What “Tools” Are Available for DR?

- The obvious first choices:
  - HVAC systems
    - Setpoints
    - Thermal energy storage
  - Lighting
- Perhaps you have considered:
  - Plug load management
  - General overall energy conservation effects
- Other more unique considerations
  - Non-traditional thermal energy storage (pre-cooling chilled water supply for example)



Organisers:



International Co-owners:



Sustainable Buildings and Climate Initiative  
Promoting Policies and Practices for Sustainability



Global Alliance  
for Buildings and  
Construction



# August 2016 Testing Example

- Changed zone setpoints by +1.7°C (3°F)
- Changed supply air setpoint also + 1.7°C
- Changed upper limit for AHU fan speed from 100% to 90% of maximum (when possible)
- Step schedule change in network chilled water supply temperature, pre-cooling first before ADR to 3.9°C, then letting temperature rise to 7.2°C during ADR
- Energy consumption monitoring and thermal comfort surveys: Test date compared to baseline date (day before)



Organisers:




International Co-owners:





# August 2016 Testing Results



Organisers:



International Co-owners:



# Lessons Learned from this Testing

- Could temperature setpoints overall could be altered, or at least during higher cost time periods?
- Timing and scheduling
  - What are the optimal setpoint changes?
  - What times to start and stop?
  - How to avoid the rebound effect ('soft-start')?
- Most difficult... Need to be adaptable to the technologies in place
  - How to implement with automation and controls not designed for 'automated' demand response



Organisers:



International Co-owners:




Sustainable Buildings and Climate Initiative  
Promoting Policies and Practices for Sustainability



Global Alliance  
for Buildings and  
Construction

# Next Steps: Thermal Comfort Testing in Real World (How Far Can We Go?)



# Thank you

Tom Lawrence  
lawrence@engr.uga.edu



Organisers:



International Co-owners:



Sustainable Buildings and Climate Initiative  
Promoting Policies and Practices for Sustainability

