

Innovative building technologies and technical equipment towards sustainable construction – a comparative LCA and LCC assessment

Presenter: **Alexander Passer**, Graz University of Technology

Co-Authors: Gernot Fischer, Graz University of Technology,
Petra Sölkner, Austrian Cooperative Research &
Sebastian Spaun, Austrian Cooperative Research

Session 5.6: Green Construction Technologies (2)



Organisers:



International Co-owners:






Photo Credit: One prediction of where rising sea levels will end up at Cottesloe Beach, Western Australia. Copyright: go_greenier_oz (Flickr)



International Co-owners:




CO₂ flows from and to Austria due to trade [1]



[1] H. Schnitzer, W. Streicher, K.W. Steininger, T. Berger, C. Brunner, A. Passer, et al., Austrian Panel on Climate Change (APCC) - Austrian Assessment Report 2014 (AAR14), in: H. KROMP-KOLB, N. NAKICENOVIC, K. STEININGER, A. GOBIET, H. FORMAYER, A. KÖPPL, et al. (Eds.), Austrian Panel Clim. Chang. - Austrian Assess. Rep. 2014, Verlag der Österreichischen Akademie der Wissenschaften, 2014: p. 1097. <http://hw.oew.ac.at/7699-2> (accessed October 2, 2014).



Growing interest – Trends



- "embodied energy" & "buildings"
- "embodied carbon" & "buildings"
- "carbon footprint" & "buildings"



Energy in Buildings and Communities Programme

Source: Litzkendorf T., SB13 Graz, IEA Energy in Buildings and Communities Programme Implementing Agreement Annex 57, -Evaluation of Embodied Energy and Carbon Dioxide Emissions for Building Construction



Aim of the project

- Sustainability assessments include the assessment of environmental and economic performance
- However: Lack of the influence of different **construction techniques, technical building equipment and energetic standards**, reflecting the existing technical variety



Organisers:



International Co-owners:













Sustainable Buildings and Climate Initiative
Promoting Policies and Practices for Sustainability




The case study - single family house in 45 variations

- Construction technique (brick, concrete, wood-chip concrete and prefab timber wood construction)
- Heating demand (low to plus energy)
- HVAC technical building systems (pellets, heat pump, solar heating and photovoltaic)
- -> Model that represents the existing technical variety



- | | | | |
|---|---|---|--|
|  | External Wall |  | Energy supply |
|  | Top floor ceiling |  | Energy-efficient equipment |
|  | Basement floor ceiling |  | Solar thermal collectors (hot water & heating) |
|  | Window |  | Photovoltaic |
|  | Controlled ventilation with heat recovery | | |



Design options: construction and insulation materials

Construction material		Insulation type with symbol			
		EPS	Rock wool insulation	Wood-fibre insulation	Without additional insulation
Brick	B	E			1
Concrete	C	E			
Mantle block (wood-concrete)	M	E		W	1
Wood solid	Ws		R		
Wood-frame construction	Wf		R		



Design options: Technical systems

Technical system	Low-energy standard			Passive-house standard		
	40 [kWh/m ² a] HWB _{ref}			10 [kWh/m ² a] HWB _{ref}		
	x-L-x-H	x-L-x-P	x-S-x-Si	x-P-x-H	x-P-x-P	x-E-x-H
Pellet boiler		Pellet boiler 10 kW	Single item (logs) 25 kW		Pellet boiler 10 kW	
Heat pump	Ground-water 10 kW _{th}			Compact unit Air-Air 1.8 kW		Compact unit Air-Air 1.8 kW
Solar thermal panels			Panel area 45 m ²			Panel area 10 m ²
PV panels						61 m ² PV panels, 6 kWp
Floor heating	yes	yes	yes		yes	
Additive system (backup)				Electric radiator 6 units		Electric radiator 6 units
Mechanical ventilation incl. heat-recovery				yes	yes	yes
Storage system (heating and hot water)	170 l Buffer storage	1000 l Heating storage 200 l WW-storage	7000 l Heating storage 300 l WW-storage	200 l Buffer storage	1000l Heating storage 200 l WW-storage	500 l WW-storage



Organisers:




International Co-owners:



Methods



- Life cycle assessment (LCA)
 - Bill of quantities, energy performance ...
- Life cycle costing (LCC)
 - Detailed cost calculations




Organisers:




International Co-owners:



Global Warming Potential [kg CO₂/sqm*a]



B6 environmental impacts



Energy standards

NEH

SH

PH

PEH





Organisers:



International Co-owners:



LCA results for the technical systems




Organisers:



International Co-owners:



Total environmental impacts





Organisers:



International Co-owners:




Sustainable Buildings and Climate Initiative
Promoting Policies and Practices for Sustainability




Global Alliance
for Buildings and
Construction


LCC




NPV




LCC Results overall / house



LCC results / sqm



LCC Results / sqm / phase



Research perspectives

- Methodical issues (sensitivity & uncertainty):
- Accounting rules for energy delivery (i.e. 1:1, or?) & accounted energy supply mix (AT, EU, UCTE, ?)
- Dynamic LCA (e.g. changes in future energy supply mixes)
- Choice FU LCA vs. LCC (GFA vs. NFA)
- LCC-parameter (energy prices, discount rates, etc.)
- Data quality & methods are “ready to be included in “real life” decision making process!



Organisers:



International Co-owners:



Sustainable Buildings and Climate Initiative
Promoting Policies and Practices for Sustainability



Conclusions

- High optimisation **potential** - spread in LCC app. -20% vs. LCA -86%
- However, variation of the technical building equipment lead to a higher improvement potential then the use of different construction techniques (LCA)
- Results also indicate that the use of a plus energy standard does not prove to be optimal in all cases (LCA & LCC)
- “Ranked order” in LCA and LCC do not correspond
- ->No “one” best option in general



Organisers:



International Co-owners:



Sustainable Buildings and Climate Initiative
Promoting Policies and Practices for Sustainability



Global Alliance
for Buildings and
Construction

Thanks to all partners!

The authors would like to thank all partners from the research project “Ökovergleiche” which served as the basis for the case study in this paper.

Innovative Gebäudekonzepte im ökologischen und ökonomischen Vergleich über den Lebenszyklus

<http://www.hausderzukunft.at/results.html/id6529>

DI Petra Johanna Sölkner, DI (FH) Isabella Hofer, DI (FH) Kevin Koke BTI – Bautechnisches Institut Linz / Energie und Gebäude

DI Robert Preininger, Ing. Karin Kröll BVFS – Bautechnische Versuchs- und Forschungsanstalt Salzburg

DI Dr. techn. Franz Dolezal, Mag. Christina Spitzbart HFA – Holzforschung Austria

DI Sebastian Spaun, Mag. Dr. Felix Papsch VOZ – Vereinigung der österr. Zementindustrie / Technologie & Umwelt

Mag. Andreas Oberhuber FGW – Forschungsgesellschaft für Wohnen, Bauen, Planen

Mag. Anja Karlsson OFI – Österreichisches Forschungsinstitut für Chemie und Technik

Mag. Hildegund Figl IBO – Österreichisches Institut für Baubiologie und Bauökologie

Univ.-Prof. DI Dr. Peter Maydl, Ass.-Prof. DI Dr. Alexander Passer, MSc, DI Gernot Fischer TU Graz / Institut für Materialprüfung und Baustofftechnologie

The authors would also like to thank all participants of the IEA EBC Annex 57 project (<http://www.annex57.org/>) for their valuable input for the preparation of the case study as part of the Austrian contribution to the IEA EBC Annex 57, which is financially supported by FFG (4069100) and BMVIT.



Greetings from Graz



Stay with
sustainability –

it is the only
way!



Organisers:



International Co-owners:



Thank you



Organisers:



International Co-owners:



Calculation parameters for LCC

Electricity price	0,17 €/kWh
Pellets price	0,25 €/kg
Wood price	0,16 €/kg
Discount rate	5,5 %
Inflation rate	2,0 %
Escalation rate	4,0 %



Organisers:



International Co-owners:



Assessed environmental indicators

Symbol	Indicator	Unit
AP	Acidification potential on soil and water	kg (SO ₂) ²⁻ eq /m ² a
EP	Eutrophication potential	kg (PO ₄) ³⁻ eq /m ² a
ODP	Ozone depletion potential	kg CFC-11 eq /m ² a
POCP	Photochemical oxidants creation potential	kg C ₂ H ₄ eq /m ² a
GWP	Global warming potential	kg CO ₂ eq /m ² a
CED non ren	Cumulative energy demand non renewable	MJ /m ² a
CED ren	Cumulative energy demand renewable	MJ /m ² a

Schematic presentation of demand/supply balance of a Net ZEB




Fig. 1. Schematic presentation of demand/supply balance of a Net ZEB [11].

Berggren, Björn ; Hall, Monika ; Wall, Maria: LCE analysis of buildings – Taking the step towards Net Zero Energy Buildings. In: Energy and Buildings Bd. 62, Elsevier B.V. (2013), S. 381–391 — <http://dx.doi.org/10.1016/j.enbuild.2013.02.063>

Net ZEB ... Net Zero Energy Buildings



International Co-owners:

